#### Instructions

Congratulations on purchasing this quality ALOGIC product. To get the most out of your purchase, please take the time to read these instructions before use.

This Product supports the latest USB-C Power delivery (PD) charging standard to allow high power USB-C devices such as Ultrabook, Chromebook, MacBook Air/Pro, tablets & phones to be charged at up to 30W or just can easily charge USB-C enabled device to up to 20W.

This charger also allows you to simultaneously charge up to two USB devices through USB-C ports. USB-C Power Delivery is a new, multi-voltage charging standard that dynamically negotiates power output over a USB-C connection allowing you to recharge a wide range of compatible devices safely and efficiently from a single charger.

#### Using the Charger

(Refer to the images on the previous pages)

Plug the wall charger into a power outlet.

Connect your Ultrabook, Chromebook, MacBook, tablet, phone or other high-powered devices such as game console to the USB-C outlet. This outlet will charge devices at up to 30W.

some tablets to charge at full speed.

Use a USB-C 5A rated cable to ensure the Tablet or smartphone charges at the fastest speeds available.

Connect lower powered USB-C devices such as phones to the USB-C outlet. The second USB-C port will charge devices at up to 20W.

Unplugging your devices when they have finished charging is recommended to prolong the life of the batteries.

### Note

The USB-C port can charge devices at up to 30W when used on its own. When both ports are in use the maximum output vanilable is reduced to 20W. Any device plugged to the top USB-C Port can be charged at up to 20W when any device is plugged into the bottom USB-C port for charging then USB-C port downgrades to 20W giving the total output of 40W across both the USB-C ports.

#### Troubleshooting

Problem	Solution
Devices charges slowly	Ensure you connect high powered devices such as Tablets and smartphones to the top USB-C port. This port is designed for high power charging and provides more power than the USB-C port below it.     Ensure you use a USB-C cable rated at 3A or above when charging. Most USB-C cables support charging at up to 3A (60W), but some only support lower charging currents and will not allow



# 40W Rapid Power 2 Port USB-C GaN Charger



Quick Start Guide














USB-C charging outlet - 30W max

Power indicator



## Specifications

Model	WCG2X40-ANZ WCG2X40-SGR-ANZ
Dimensions	47.5x 47.3 x 27.7mm (H x D x W)
Weight	110g
Output	Single Port USB-C #1 #2 single output: PD3.0 (5V,9V/3A, 12V/2.52A) 30W* Dual Port USB-C#1: (5V/3A, 9V/2.22A, 12V/1.67A) 20W USB-C#2: (5V/3A, 9V/2.22A, 12V/1.67A) 20W 'Derated when both ports active as follows: USB-C #1 20W + USB-C #2 20W
Input	100-240VAC 50°60Hz 1.2A Max
Warranty	2 Years



40W Rapid Power GaN Charger User Manual

